



注：1, PIN拉力0.8kg/ MIN;其中最多允许4只PIN拉力
 低于0.8, 但必须大于0.6KG;
 2, PIN脚表面电镀;

A1	21.03.18	1, 支点从1.1加宽至1.5. 2, pin打扁高度改为0.75.
A2	21.08.01	胶体材质从PM9630改为DAP
REV	DATE	REVSIONS REC

FuXun 东莞市福讯达塑胶制品有限公司
 DONGGUAN FU XUN DA PLASTICS PRODUCTS CO., LTD
 地址：东莞市横沥镇三江工业区116栋
 TEL:0769-82218739 82218769 FAX:0769-82218929

DRAFTER	ZHANG SHAO YONG	TOLERANCE	DATE:
CHECK	WANG	0<L≤4 ±0.1	2021.8.01
APPROVED	ZHU DONG SHENG	4<L≤16 ±0.2	
		16<L≤50 ±0.3	
		PIN PITCH ±0.2	

DRAWING TITLE:	CASE-24	TERMIAL DIMENTION:	----	ANGLE:	±1°
MODLE NAME:	FX-S-CASE005	TERMINAL MATERIAL:	CP WIRE	UNIT:	mm
SPECIFICATION:	24 PIN	UL RATING:	94V-0	SCALE:	1 : 1
BOBBING MATERIAL:	DAP -8200	PULLING STRENGTH:	0.8Kg/MIN	REV:	A/2